PRODUCT OF THERMACUT' THE CUTTING COMPANY'

EX-TRAFIRE45SD PROFESSIONAL AND VERSATILE PLASMA CUTTING SYSTEM.

Last update of this page: 09/06/2021. See Revision history for details.





EX-IRAFIRE

PLASMA CUITTING SYSTEM BY THERMACUT®

EX-TRAFIRE[®]**45SD**



SIMPLE OPERATION



+ Bright LCD system information and control panel + Easily accessible, protected filter regulator + Engineered for professionals and demanding beginners

EX-TRA PERFORMANCE



76

- + Cutting, gouging, grid mode Exact cuts
- +Industry leading blue LCD display

HIGHEST APPLICATION FLEXIBILITY



- + Plate thicknesses up to 25 mm + +Lightweight, exceptionally portable
- +TCS quick change flexible torch packages
- + Suitable for generator use

BEST COST-EFFECTIVENESS




+ Significantly lower investment + High consumable lifetime Lower running costs

Last update of this page: 09/06/2021. See Revision history for details.

SPECIFICATIONS

Input voltage (VAC) Output current (A) Plasma gas Certification CE, C-TICK, CCC Modes Frequency (Hz)	1x120 V +-15 % 20-25 CE	1x230 V +-15 % 20-45 Compressed air	3x400 V +-15 % 20-45	
Plasma gas Certification CE, C-TICK, CCC Modes		Compressed air	20-45	
Certification CE, C-TICK, CCC Modes	CE			
Modes	CE			
		CE/C-TICK	CE/C-TICK	
Frequency (Hz)		CUTTING / GOUGING / GRID C	UTTING	
		50/60		
Maximum input power (kVA)	4,4	7,59	6,48	
Output voltage (VDC)		145		
Duty cycle @ 40 °C 40	%@25A/100%@16A	50 % @ 45 A / 10 0% @ 32 A	80 % @ 45 A / 100 % 40 A	
Dimension (l × h × w) mm		469 x 228 x 177		
Weight (KG)		12,7		
Recommended cutting capacity (mm)	8		12	
Severance cutting capacity (mm)	12		25	
Piercing cutting capacity (mm)	10		10	
Air flow @ (lpm/bar)		90 @ 4.8		
Maximum input pressure (bar/psi)		10/145		
Protection level	IP23S			
Insulation class	F			
CNC interface	YES			
Industry 4.0		NO		
Type of hand torch		FHT-EX®45TTH		
Type of machine torch		FHT-EX®45TTM		

MILD STEEL CUTTING CAPACITY IN MILLIMETRES



STERED TRADEMARKS OF THERMACUT

EX-TRAFIRE[®]45SD

Last update of this page: 09/06/2021. See Revision history for details.

EX-TRAFIRE[®]45SD

ORDERING INFORMATION

Description	Length	Part No.
MANUAL PLASMA CUTTING SYSTEMS		
EX-TRAFIRE®45SD/CE/3x400 V Hand System/FHT-EX®45TTH 5m/H Starter Kit	5 m	EX-2-010-011
EX-TRAFIRE®45SD/CE/3x400 V Hand System/FHT-EX®45TTH 8m/H Starter Kit	8 m	EX-2-010-012
EX-TRAFIRE®45SD/CE/3x400 V Hand System/FHT-EX45®TTH 15m/H Starter Kit	15 m	EX-2-010-013
EX-TRAFIRE®45SD/CE/1x110/230 V Hand System/FHT-EX45®TTH 5m/H Starter Kit	5 m	EX-2-010-020
EX-TRAFIRE®45SD/CE/1x110/230 V Hand System/FHT-EX45®TTH 8m/H Starter Kit	8 m	EX-2-010-021
EX-TRAFIRE®45SD/CE/1x110/230 V Hand System/FHT-EX45®TTH 15m/H Starter Kit	15 m	EX-2-010-022
MECHANIZED PLASMA CUTTING SYSTEMS		
EX-TRAFIRE®45SD/CE/3x400 V Machine System/FHT-EX45®TTM 5m/M Starter Kit	5 m	EX-2-011-008
EX-TRAFIRE®45SD/CE/3x400 V Machine System/FHT-EX45®TTM 8m/M Starter Kit	8 m	EX-2-011-009
EX-TRAFIRE®45SD/CE/3x400 V Machine System/FHT-EX45®TTM 15m/M Starter Kit	15 m	EX-2-011-010
EX-TRAFIRE®45SD/CE/1x110/230 V Machine System/FHT-EX45®TTM 5m/M Starter Kit	5 m	EX-2-011-014
EX-TRAFIRE®45SD/CE/1x110/230 V Machine System/FHT-EX45®TTM 8m/M Starter Kit	8 m	EX-2-011-015
EX-TRAFIRE®45SD/CE/1x110/230 V Machine System/FHT-EX45®TTM 15m/M Starter Kit	15 m	EX-2-011-016
PLASMA POWER SUPPLY UNITS		
EX-TRAFIRE®45SD/CE/3x400 V power supply unit (fully-equipped*)		EX-2-001-030
EX-TRAFIRE®45SD/CE/1x110/230 V power supply unit (fully-equipped*)		EX-2-001-024
Ilv-equipped=CNC interface & Serial interfaceport (CAN bus)		
Illy-equipped=CNC interface & Serial interfaceport (CAN bus)		



FRONT VIEW

AVAILABLE BULK PACKS

Description	Pcs	Part No.
Bulk Pack-Electrode - 25 pcs	1	EX-2-434-201
Bulk Pack-Nozzle - 25 pcs	1	EX-2-435-201
Bulk Pack - Hand (Contact) Shield - 18 pcs	1	EX-2-436-201
Bulk Pack - Machine Shield - 18 pcs	1	EX-2-437-201

ACCESSORIES

Description	Pcs	Part No.
DN 7.2 ES Quick Connect Plug with female thread G 1/4"	1	EX-0-802-000
DN 7.2 ES Quick Connect Plug with male thread G 1/4"	1	EX-0-802-001
DN 7.2 ES Quick Connect Coupling with male thread G 1/4"	1	EX-0-802-002
Grease 25 ml	1	EX-0-805-001
Filter-EX Compressed Air Filter	1	EX-0-804-001
Filter-EX Air Filter Cartridge	8	EX-0-804-002

THERMACUT®, THE CUTTING COMPANY®, FHT-EX®, EX-TRAFIRE®, EX-TRACK®, EX-TRABEAM® AND EX-TRAFLAME® ARE REGISTERED TRADEMARKS OF THERMACUT, K.S. AND MAY BE REGISTERED IN CZECH REPUBLIC AND/OR OTHER COUNTRIES. ALL OTHER TRADEMARKS ARE PROPERTIES OF THEIR RESPECTIVE OWNERS.

Last update of this page: 09/06/2021. See Revision history for details.

EMAIL: SALES@THERMACUT.CZ

EMAIL: COMPLAINT@THERMACUT.CZ

EX-TRAFIRE[®]45SD



BACK VIEW



SIDE VIEW

Last update of this page: 09/06/2021. See Revision history for details.

EMAIL: INFO@THERMACUT.CZ